NSN 5962-00-434-2757



Memory Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-00-434-2757 **Body Length:** Between 0.360 inches and 0.410 inches **Body Width:** Between 0.240 inches and 0.280 inches **Body Height:** Between 0.030 inches and 0.070 inches **Maximum Power Dissipation Rating:** 150.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and w/enable and positive outputs and dynamic **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** P-type metal oxide-semiconductor logic **Input Circuit Pattern:** 14 input **Terminal Surface Treatment:** Gold **Voltage Rating And Type Per Characteristic:** 0.3 volts power source **Memory Device Type:** Rom **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold **Test Data Document:** 13499-351-8003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 24 flat leads Shelf Life: N/a

Demilitarization: Yes - demil/mli

Unit Of Measure:

NSN 5962-00-434-2757

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0