NSN 5962-00-434-3055

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-434-3055
Body Length:
Between 0.240 inches and 0.265 inches
Body Width:
Between 0.240 inches and 0.265 inches
Body Height:
Between 0.030 inches and 0.080 inches
Maximum Power Dissipation Rating:
200.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and positive outputs and low power
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Diode-transistor logic
Input Circuit Pattern:
Hex 1 input
Design Function And Quantity:
6 inverter, digital
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
30.00 nanoseconds propagation delay time, low to high level output and 80.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
30221-44a340313 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig: A458a0

Yes - demil/mli