NSN 5962-00-434-3072

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-434-3072 **Body Length:** Between 1.208 inches and 1.232 inches **Body Width:** 0.530 inches **Body Height:** Between 0.120 inches and 0.165 inches **Maximum Power Dissipation Rating:** 1.3 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and negative outputs and w/buffered output and w/decoded output and programmable and programmed **Inclosure Material:** Ceramic and metal **Inclosure Configuration:** Dual-in-line **Output Logic Form:** P-type metal oxide-semiconductor logic **Input Circuit Pattern:** 10 input **Terminal Surface Treatment:** Gold **Voltage Rating And Type Per Characteristic:** 0.5 volts power source **Time Rating Per Chacteristic:** 600.00 nanoseconds propagation delay time, low to high level output **Memory Device Type:** Rom **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold **Test Data Document:** 12464-b77t0197 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 24 printed circuit Shelf Life:

N/a

Unit Of Measure:

NSN 5962-00-434-3072

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0