

View Online at <https://aerobasegroup.com/nsn/5962-00-434-3135>

**Body Outside Diameter:**

0.550 inches

**Body Height:**

Between 0.050 inches and 0.070 inches

**Maximum Power Dissipation Rating:**

150.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Monolithic and hermetically sealed and w/enable

**Inclosure Material:**

Glass and metal

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

P-type metal oxide-semiconductor logic

**Input Circuit Pattern:**

2 input

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

0.3 volts power source

**Time Rating Per Characteristic:**

80.00 nanoseconds propagation delay time, low to high level output and 80.00 nanoseconds propagation delay time, high to low level output

**Memory Device Type:**

Rom

**Precious Material And Location:**

Terminal and top and bottom pkg surfaces gold

**Precious Material:**

Gold

**Test Data Document:**

13499-351-8102 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

22 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0