

View Online at <https://aerobasegroup.com/nsn/5962-00-434-3152>

Body Outside Diameter:

0.556 inches

Body Height:

Between 0.049 inches and 0.068 inches

Maximum Power Dissipation Rating:

150.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and resettable and negative outputs and positive outputs

Inclosure Material:

Glass and metal

Inclosure Configuration:

Flat pack

Output Logic Form:

P-type metal oxide-semiconductor logic

Input Circuit Pattern:

2 input

Design Function And Quantity:

1 generator

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

0.3 volts power source

Time Rating Per Characteristic:

80.00 nanoseconds propagation delay time, low to high level output and 80.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Body and terminal surfaces gold

Precious Material:

Gold

Test Data Document:

13499-351-8171 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

34 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0