## NSN 5962-00-436-0750

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-436-0750
Body Length:
Between 0.240 inches and 0.290 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.030 inches and 0.070 inches
Maximum Power Dissipation Rating:
300.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and high voltage and high gain and negative outputs and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
Dual 3 input
Design Function And Quantity:
2 comparator, voltage, differential
Case Outline Source And Designator:
T0-91 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
60.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
12464-b77t0139 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
10 flat leads
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

Fiig:

A458a0