NSN 5962-00-436-1645

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-436-1645
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
250.0 milliwatts
Operating Tempurature Range:
-30.0/+75.0 degrees celsius
Storage Tempurature Range:
-55.0/+125.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and positive outputs and expandable
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Dual 5 input
Design Function And Quantity:
2 driver, lamp, incandescent
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
18.0 volts power source
Time Rating Per Chacteristic:
500.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
97384-5339-093015 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig:

A458a0

Yes - demil/mli