## NSN 5962-00-436-6445

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-436-6445 **Body Length:** Between 0.240 inches and 0.275 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.030 inches and 0.070 inches **Maximum Power Dissipation Rating:** 11.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and expandable and bipolar and positive outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Diode-transistor logic **Input Circuit Pattern:** 8 input **Design Function And Quantity:** 

1 gate, nand

**Case Outline Source And Designator:** 

T0-86 joint electron device engineering council

**Terminal Surface Treatment:** 

Solder

Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

**Time Rating Per Chacteristic:** 

35.00 nanoseconds propagation delay time, low to high level output

**Test Data Document:** 

37695-618999 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:** 

1 flat leads

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

## **NSN 5962-00-436-6445**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0