

View Online at <https://aerobasegroup.com/nsn/5962-00-439-0883>

**Body Length:**

Between 0.337 inches and 0.350 inches

**Body Width:**

Between 0.200 inches and 0.300 inches

**Body Height:**

Between 0.008 inches and 0.100 inches

**Maximum Power Dissipation Rating:**

22.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and low power and edge triggered and w/clear

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

Dual 4 input

**Design Function And Quantity:**

2 flip-flop, j-k, clocked and 2 flip-flop, j-k, master slave

**Case Outline Source And Designator:**

-0-004-aa joint electron device engineering council

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-1.5 volts power source and 5.5 volts power source

**Time Rating Per Characteristic:**

125.00 nanoseconds propagation delay time, low to high level output and 200.00 nanoseconds propagation delay time, high to low level output

**Terminal Type And Quantity:**

14 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0