## NSN 5962-00-439-0931

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-439-0931

| g  |
|--|
| Body Length:   |
| Between 0.660 inches and 0.785 inches  |
| Body Width:  |
| Between 0.220 inches and 0.280 inches  |
| Body Height:   |
| Between 0.140 inches and 0.180 inches  |
| Maximum Power Dissipation Rating:  |
| 750.0 milliwatts   |
| Operating Tempurature Range:   |
| +0.0/+75.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| Features Provided:   |
| Monolithic and hermetically sealed and high gain and negative outputs and positive outputs |
| Inclosure Material:  |
| Ceramic and glass  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Input Circuit Pattern:   |
| Dual 4 input   |
| Design Function And Quantity:  |
| 2 amplifier, operational, general purpose  |
| Case Outline Source And Designator:  |
| T0-116 joint electron device engineering council   |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| -18.0 volts power source and 18.0 volts power source                                       |
| Terminal Type And Quantity:  |
| 14 printed circuit   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |

A458a0