## NSN 5962-00-448-6045

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-448-6045
Body Length:
Between 0.360 inches and 0.410 inches
Body Width:
Between 0.240 inches and 0.280 inches
Body Height:
Between 0.030 inches and 0.070 inches
Maximum Power Dissipation Rating:
150.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and w/enable
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
P-type metal oxide-semiconductor logic
Input Circuit Pattern:
5 input
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
-30.0 volts power source and 0.3 volts power source
Time Rating Per Chacteristic:
80.00 nanoseconds propagation delay time, low to high level output and 80.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Test Data Document:
13499-580-6003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
24 flat leads
Shelf Life:
N/a

Yes - demil/mli

**Unit Of Measure:** 

Demilitarization:

## **NSN 5962-00-448-6045**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0