## NSN 5962-00-451-3870

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-451-3870

view Offilite at https://aerobasegroup.com/hsh/5502-00-451-5070
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
0.180 inches
Maximum Power Dissipation Rating:
1.3 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
W/clear and w/preset and hermetically sealed and burn in
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
5 input
Design Function And Quantity:
2 flip-flop, j-k, clocked, master slave
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
25.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
00752-385079 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:

**Demilitarization:** Yes - demil/mli

## **NSN 5962-00-451-3870**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0