

View Online at <https://aerobasegroup.com/nsn/5962-00-454-8288>

Body Outside Diameter:

Between 0.335 inches and 0.370 inches

Body Height:

Between 0.165 inches and 0.185 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+200.0 degrees celsius

Features Provided:

Monolithic and hermetically sealed and programmed and bipolar and w/enable and positive outputs

Inclosure Material:

Glass and metal

Inclosure Configuration:

Can

Output Logic Form:

P-type metal oxide-semiconductor logic

Input Circuit Pattern:

3 input

Design Function And Quantity:

2 shift register, dynamic

Case Outline Source And Designator:

T0-99 joint electron device engineering council

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-25.0 volts power source

Time Rating Per Characteristic:

200.00 nanoseconds propagation delay time, low to high level output and 200.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

19133-902140 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0