## NSN 5962-00-455-3465

Linear Microcircuit - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5962-00-455-3465                |
|--|
| Body Outside Diameter:   |
| Between 0.335 inches and 0.370 inches  |
| Body Height:   |
| Between 0.165 inches and 0.185 inches  |
| Maximum Power Dissipation Rating:  |
| 680.0 milliwatts   |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| Features Provided:   |
| Monolithic and hermetically sealed and negative outputs and positive outputs |
| Inclosure Material:  |
| Glass and metal  |
| Inclosure Configuration:   |
| Can  |
| Input Circuit Pattern:   |
| 4 input  |
| Design Function And Quantity:  |
| 1 amplifier, operational, general purpose                                    |
| Case Outline Source And Designator:  |
| T0-99 joint electron device engineering council                              |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:                                  |
| 36.0 volts power source  |
| Terminal Type And Quantity:  |
| 8 pin  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |

A458a0