# NSN 5962-00-455-3510

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-455-3510

#### **Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

#### **Body Height:**

Between 0.165 inches and 0.185 inches

# **Maximum Power Dissipation Rating:**

500.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and negative outputs and positive outputs and high speed

#### **Inclosure Material:**

Glass and metal

#### **Inclosure Configuration:**

# Can

**Input Circuit Pattern:** 

2 input

### **Design Function And Quantity:**

1 comparator, voltage, differential

#### **Case Outline Source And Designator:**

T0-99 joint electron device engineering council

# **Terminal Surface Treatment:**

Gold

#### **Time Rating Per Chacteristic:**

40.00 nanoseconds propagation delay time, low to high level output

#### **Precious Material And Location:**

Terminals gold

#### **Precious Material:**

Gold

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### **Demilitarization:**

Yes - demil/mli

Fiig:

A458a0