NSN 5962-00-455-7630

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-455-7630

3 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -
Body Length:
Between 0.240 inches and 0.275 inches
Body Width:
Between 0.160 inches and 0.185 inches
Body Height:
Between 0.030 inches and 0.070 inches
Maximum Power Dissipation Rating:
60.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and high speed and negative outputs and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 driver, line
Case Outline Source And Designator:
T0-85 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
5.00 nanoseconds propagation delay time, low to high level output and 5.00 nanoseconds propagation delay time, high to low level output
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0