## NSN 5962-00-459-4441

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-459-4441

Body Le	- 44
DOOV I E	nam

Between 0.240 inches and 0.290 inches

**Body Width:** 

Between 0.120 inches and 0.150 inches

**Body Height:** 

Between 0.030 inches and 0.070 inches

**Operating Tempurature Range:** 

+0.0/+100.0 degrees celsius

**Storage Tempurature Range:** 

-65.0/+150.0 degrees celsius

**Features Provided:** 

Monolithic and hermetically sealed and positive outputs

**Inclosure Material:** 

Glass and metal

**Inclosure Configuration:** 

Flat pack

**Input Circuit Pattern:** 

2 input

**Design Function And Quantity:** 

1 amplifier, video and 1 amplifier, wideband

**Case Outline Source And Designator:** 

T0-89 joint electron device engineering council

**Terminal Surface Treatment:** 

Gold

Voltage Rating And Type Per Characteristic:

8.0 volts power source

**Time Rating Per Chacteristic:** 

12.00 nanoseconds propagation delay time, low to high level output and 12.00 nanoseconds propagation delay time, high to low level output

**Special Features:** 

Formed leads

**Precious Material And Location:** 

Terminal surface gold

**Precious Material:** 

Gold

**Test Data Document:** 

49956-358614 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

10 flat leads

Shelf Life:

N/a

Unit Of Measure:

## NSN 5962-00-459-4441

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0