

View Online at <https://aerobasegroup.com/nsn/5962-00-459-5786>

**Body Length:**

Between 0.688 inches and 0.718 inches

**Body Width:**

Between 0.225 inches and 0.275 inches

**Body Height:**

0.120 inches

**Maximum Power Dissipation Rating:**

88.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Monolithic and positive outputs and synchronous and hermetically sealed

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Diode-transistor logic

**Input Circuit Pattern:**

Quad 2 input

**Design Function And Quantity:**

4 gate, nand-nor

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

5.5 volts power source

**Time Rating Per Characteristic:**

48.00 nanoseconds propagation delay time, low to high level output and 48.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

97942-580r889 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

14 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0