NSN 5962-00-460-5745

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-460-5745 **Body Length:** Between 0.750 inches and 0.785 inches **Body Width:** Between 0.245 inches and 0.271 inches **Body Height:** Between 0.140 inches and 0.180 inches **Maximum Power Dissipation Rating:** 150.0 milliwatts **Operating Tempurature Range:** +0.0/+75.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and complementary outputs and w/buffered output and positive outputs and high speed **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 10 input **Design Function And Quantity:**

2 multiplexer

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Chacteristic:

36.00 nanoseconds propagation delay time, low to high level output and 36.00 nanoseconds propagation delay time, high to low level output

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0