

View Online at <https://aerobasegroup.com/nsn/5962-00-461-0581>

Body Length:

Between 0.250 inches and 0.260 inches

Body Width:

Between 0.140 inches and 0.150 inches

Body Height:

Between 0.035 inches and 0.050 inches

Maximum Power Dissipation Rating:

275.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and positive outputs and darlington-connected

Inclosure Material:

Glass and metal

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

5 input

Design Function And Quantity:

1 adder, full, binary

Case Outline Source And Designator:

T0-84 joint electron device engineering council

Time Rating Per Characteristic:

40.00 nanoseconds propagation delay time, low to high level output and 42.00 nanoseconds propagation delay time, high to low level output

Special Features:

Formed leads; insulator furnished

Precious Material And Location:

Terminals gold and body gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0