

View Online at <https://aerobasegroup.com/nsn/5962-00-461-5190>

Body Length:

Between 0.235 inches and 0.255 inches

Body Width:

Between 0.180 inches and 0.210 inches

Body Height:

Between 0.030 inches and 0.070 inches

Maximum Power Dissipation Rating:

60.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and monolithic and positive outputs

Inclosure Material:

Ceramic

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Quad 2 input

Design Function And Quantity:

4 gate, nand

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

8.0 volts power source

Time Rating Per Characteristic:

20.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0