# NSN 5962-00-461-5190

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-461-5190

# **Body Length:**

Between 0.235 inches and 0.255 inches

## Body Width:

Between 0.180 inches and 0.210 inches

## **Body Height:**

Between 0.030 inches and 0.070 inches

## **Maximum Power Dissipation Rating:**

60.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

### **Features Provided:**

Hermetically sealed and burn in and monolithic and positive outputs

#### Inclosure Material:

Ceramic

### Inclosure Configuration:

Flat pack

### **Output Logic Form:**

Transistor-transistor logic

## Input Circuit Pattern:

Quad 2 input

### **Design Function And Quantity:**

4 gate, nand

### **Terminal Surface Treatment:**

Solder

### Voltage Rating And Type Per Characteristic:

8.0 volts power source

### Time Rating Per Chacteristic:

20.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level output

### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

### Terminal Type And Quantity:

14 flat leads

### Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0