## NSN 5962-00-462-3623

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-462-3623
Body Length:
Between 0.240 inches and 0.270 inches
Body Width:
Between 0.165 inches and 0.195 inches
Body Height:
Between 0.040 inches and 0.070 inches
Maximum Power Dissipation Rating:
40.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+200.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and expandable
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 2 wide 2 input
Design Function And Quantity:
2 gate, and-or
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
22.00 nanoseconds propagation delay time, low to high level output and 22.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
04655-15-107407 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

Fiig: A458a0

Yes - demil/mli