NSN 5962-00-462-7491

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-462-7491

| The state of the s |
|--|
| Body Length: |
| Between 0.710 inches and 0.785 inches |
| Body Width: |
| Between 0.240 inches and 0.280 inches |
| Body Height: |
| Between 0.140 inches and 0.180 inches |
| Operating Tempurature Range: |
| +0.0/+75.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and monolithic and positive outputs and gated output |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| Hex 1 input |
| Design Function And Quantity: |
| 6 converter |
| Time Rating Per Chacteristic: |
| 13.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level |
| output |
| Test Data Document: |
| 06845-4019159 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |