NSN 5962-00-462-7746

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-462-7746

Body Length: 0.810 inches **Body Width:** Between 0.220 inches and 0.295 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 730.0 milliwatts **Operating Tempurature Range:** +0.0/+100.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and complementary outputs and w/open collector **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 3 input **Design Function And Quantity:** 2 driver, line **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Time Rating Per Chacteristic:** 15.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level output and 5000.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 82577-932020 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life:

Unit Of Measure:

N/a

Demilitarization:

Yes - demil/mli

Fiig:

A458a0