NSN 5962-00-462-7747

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-462-7747 **Body Length:** 0.800 inches **Body Width:** Between 0.220 inches and 0.280 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 375.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and bipolar and positive outputs and w/enable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 6 channel **Design Function And Quantity:** 6 driver, switch, field effect transistor **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 30.0 volts power source **Time Rating Per Chacteristic:** 600.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 82577-932077 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Yes - demil/mli

Fiig:

A458a0