NSN 5962-00-465-4822

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-465-4822

Body Outside Diameter:
Between 0.355 inches and 0.370 inches
Body Height:
Between 0.170 inches and 0.180 inches
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Positive outputs and w/strobe and hermetically sealed and adjustable and negative outputs and monolithic
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
7 input
Design Function And Quantity:
1 comparator, voltage
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
8.0 volts power source
Time Rating Per Chacteristic:
85.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
12868-1012280 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
10 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A458a0
170000