## NSN 5962-00-465-4908

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-465-4908 **Body Length:** Between 0.250 inches and 0.260 inches **Body Width:** Between 0.140 inches and 0.150 inches **Body Height:** Between 0.035 inches and 0.050 inches **Maximum Power Dissipation Rating:** 400.0 milliwatts **Operating Tempurature Range:** -55.0/+135.0 degrees celsius Storage Tempurature Range: -65.0/+175.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and positive outputs and negative outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 6 input **Design Function And Quantity:** 2 receiver, line **Terminal Surface Treatment:** Gold **Time Rating Per Chacteristic:** 200.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold **Test Data Document:** 90536-7901672 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli

Fiig:

A458a0