NSN 5962-00-469-4598

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-469-4598

| Body Outside Diameter: |
|---|
| Between 0.335 inches and 0.370 inches |
| Body Height: |
| Between 0.165 inches and 0.185 inches |
| Maximum Power Dissipation Rating: |
| 500.0 milliwatts |
| Operating Tempurature Range: |
| 55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| 65.0/+150.0 degrees celsius |
| Features Provided: |
| High performance and hermetically sealed and monolithic and negative outputs and positive outputs |
| nclosure Material: |
| Metal |
| nclosure Configuration: |
| Can |
| nput Circuit Pattern: |
| 2 input |
| Design Function And Quantity: |
| 1 amplifier, operational, general purpose |
| Case Outline Source And Designator: |
| T0-99 joint electron device engineering council |
| Terminal Surface Treatment: |
| Гіп |
| Test Data Document: |
| 32577-928678 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| Yes - demil/mli |
| Filg: |
| A458a0 |
| |
| |