NSN 5962-00-469-4633

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-469-4633

Body Le	ngth:
0.375 inc	hes
Body Wi	dth:
0.250 inc	hes
Body He	ight:
Between	0.054 inches and 0.064 inches
Maximur	n Power Dissipation Rating:
450.0 mil	liwatts
Operatin	g Tempurature Range:
+0.0/+55	0 degrees celsius
Storage	Tempurature Range:
-65.0/+15	0.0 degrees celsius
Features	Provided:
Hermetic	ally sealed and monolithic and positive outputs
Inclosur	e Material:
Ceramic	and glass
Inclosur	e Configuration:
Flat pack	
Input Cir	cuit Pattern:
12 input	
Design F	unction And Quantity:
1 convert	er, digital to analog
Termina	Surface Treatment:
Gold	
Voltage	Rating And Type Per Characteristic:
7.0 volts	power source
Precious	Material And Location:
Terminal	surfaces gold
Precious	Material:
Gold	
Test Dat	a Document:
82577-93	2279 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes	any specification, standard or other document that may be referenced in a basic governing drawing)
Termina	Type And Quantity:
24 flat lea	ads
Shelf Lif	2:
N/a	
Unit Of M	leasure:
Demilita	ization:
Yes - der	nil/mli
Fiig:	
A458a0	