

View Online at <https://aerobasegroup.com/nsn/5962-00-471-2583>

Body Length:

Between 0.330 inches and 0.350 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.030 inches and 0.070 inches

Maximum Power Dissipation Rating:

60.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and hermetically sealed and positive outputs and w/enable and medium speed and resettable and edge triggered

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Dual 4 input

Design Function And Quantity:

2 flip-flop, j-k, clocked

Case Outline Source And Designator:

T0-88 joint electron device engineering council

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

6.0 volts power source

Time Rating Per Characteristic:

20.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

13499-351-7338 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0