NSN 5962-00-471-2589

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-471-2589

Body Length:
0.275 inches
Body Width:
0.195 inches
Body Height:
0.065 inches
Maximum Power Dissipation Rating:
90.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+200.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and positive outputs and medium speed
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Hex 1 input
Design Function And Quantity:
6 inverter, digital
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
20.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Test Data Document:
13499-351-7424 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:

Unit Of Measure:

NSN 5962-00-471-2589

Digital Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

