## NSN 5962-00-472-9396

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-472-9396 **Overall Width:** Between 0.490 inches and 0.525 inches **Body Length:** Between 0.330 inches and 0.350 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** 0.085 inches **Maximum Power Dissipation Rating:** 250.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and w/resistor and w/expander **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Diode-transistor logic **Input Circuit Pattern:** Dual 4 input **Design Function And Quantity:** 2 gate, nand buffer **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 8.0 volts power source **Time Rating Per Chacteristic:** 105.00 nanoseconds propagation delay time, low to high level output and 105.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 14 pin Shelf Life: N/a **Unit Of Measure:** 

Demilitarization: Yes - demil/mli

## **NSN 5962-00-472-9396**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0