NSN 5962-00-472-9785

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-472-9785

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
0.180 inches
Maximum Power Dissipation Rating:
680.0 milliwatts
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and negative outputs and positive outputs and adjustable
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
4 input
Design Function And Quantity:
1 amplifier, operational, general purpose
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
10.0 volts power source and 10.0 volts power source
Time Rating Per Chacteristic:
200.00 nanoseconds propagation delay time, high to low level output
Test Data Document:
09206-740005 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
10 pin
Shelf Life:
N/a
Unit Of Measure:
. -
Demilitarization:
Yes - demil/mli
Fiig:
A458a0