NSN 5962-00-472-9785

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-472-9785

Body Outside Diameter:

Between 0.335 inches and 0.370 inches

Body Height:

0.180 inches

Maximum Power Dissipation Rating:

680.0 milliwatts

Operating Tempurature Range:

+0.0/+75.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and hermetically sealed and negative outputs and positive outputs and adjustable

Inclosure Material:

Glass and metal

Inclosure Configuration:

Can

Input Circuit Pattern:

4 input

Design Function And Quantity:

1 amplifier, operational, general purpose

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-10.0 volts power source and 10.0 volts power source

Time Rating Per Chacteristic:

200.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

09206-740005 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

10 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0