

View Online at <https://aerobasegroup.com/nsn/5962-00-474-7893>

**Body Length:**

Between 0.740 inches and 0.780 inches

**Body Width:**

Between 0.240 inches and 0.270 inches

**Body Height:**

Between 0.135 inches and 0.165 inches

**Maximum Power Dissipation Rating:**

140.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+175.0 degrees celsius

**Features Provided:**

Monolithic and hermetically sealed and resettable and w/enable and edge triggered and positive outputs and negative outputs

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Emitter-coupled logic

**Input Circuit Pattern:**

8 input

**Design Function And Quantity:**

1 flip-flop, d-type, r-s, clocked

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-10.0 volts power source and 0.0 volts power source

**Time Rating Per Characteristic:**

18.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

49956-465800 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

14 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0