## NSN 5962-00-476-7849

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-476-7849
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
0.180 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Edge triggered and hermetically sealed and medium power and medium speed and monolithic and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Diode-transistor logic
Input Circuit Pattern:
Hex 1 input
Design Function And Quantity:
6 inverter, digital
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
8.0 volts power source
Time Rating Per Chacteristic:
80.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Test Data Document:
88818-c574000027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

## **NSN 5962-00-476-7849**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0