## NSN 5962-00-477-1622

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-477-1622 **Body Length:** 0.900 inches **Body Width:** 0.525 inches **Body Height:** 0.200 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and hybrid and negative outputs and positive outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 5 input **Design Function And Quantity:** 1 switch, driver **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -8.0 volts power source and 8.0 volts power source **Time Rating Per Chacteristic:** 10.00 nanoseconds propagation delay time, low to high level output and 10.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 94117-320019 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** Yes - demil/mli

Fiig:

A458a0