## NSN 5962-00-479-9559

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-479-9559 **Overall Width:** Between 0.740 inches and 1.000 inches **Body Length:** Between 0.240 inches and 0.260 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.050 inches and 0.065 inches **Maximum Power Dissipation Rating:** 200.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** High gain and wideband and monolithic and hermetically sealed **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 amplifier, dc **Terminal Surface Treatment:** Gold Voltage Rating And Type Per Characteristic: 10.0 volts power source **Precious Material And Location:** Terminal surfaces gold **Precious Material:** Gold **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 10 flat leads Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** Yes - demil/mli

## NSN 5962-00-479-9559

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0