NSN 5962-00-481-8664

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-481-8664 **Body Length:** Between 0.240 inches and 0.260 inches **Body Width:** Between 0.120 inches and 0.150 inches **Body Height:** Between 0.030 inches and 0.070 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Expandable and hermetically sealed and monolithic and positive outputs **Inclosure Material:** Glass and metal **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Dual 4 input **Design Function And Quantity:** 2 gate, and-or **Case Outline Source And Designator:** T0-84 joint electron device engineering council **Terminal Surface Treatment:** Gold **Voltage Rating And Type Per Characteristic:** 5.5 volts power source **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold **Test Data Document:** 11530-44-191514 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 flat leads

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-00-481-8664Digital Microcircuit - Page 2 of 2



Fiig:

A458a0