# NSN 5962-00-481-8666

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-481-8666

Bodv	l er	nath:
Douv	LCI	ıuıı.

Between 0.240 inches and 0.260 inches

**Body Width:** 

Between 0.120 inches and 0.150 inches

**Body Height:** 

Between 0.030 inches and 0.070 inches

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Expandable and hermetically sealed and monolithic and positive outputs

### **Inclosure Material:**

Glass and metal

#### **Inclosure Configuration:**

Flat pack

# **Output Logic Form:**

Transistor-transistor logic

# **Input Circuit Pattern:**

4 wide 2-2-2-3 input

# **Design Function And Quantity:**

1 gate, and-or invert

#### **Case Outline Source And Designator:**

T0-84 joint electron device engineering council

#### **Terminal Surface Treatment:**

Gold

# **Voltage Rating And Type Per Characteristic:**

5.5 volts power source

#### **Time Rating Per Chacteristic:**

10.00 nanoseconds propagation delay time, low to high level output and 10.00 nanoseconds propagation delay time, high to low level output

# **Precious Material And Location:**

Terminal surface gold

# **Precious Material:**

Gold

#### **Test Data Document:**

11530-44-191516 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# **Terminal Type And Quantity:**

14 flat leads

#### Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5962-00-481-8666

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0