NSN 5962-00-481-8676

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-481-8676

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
300.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and high gain and low power and externally compensated and negative outputs and positive outputs
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
4 input
Case Outline Source And Designator:
T0-99 joint electron device engineering council
Terminal Surface Treatment:
Gold
Time Rating Per Chacteristic:
1000.00 nanoseconds propagation delay time, low to high level output
Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Test Data Document:
11530-91-178618 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A458a0