NSN 5962-00-484-6033

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-484-6033 **Body Length:** 0.260 inches **Body Width:** 0.250 inches **Body Height:** Between 0.030 inches and 0.070 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and complementary outputs and monolithic **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 5 input **Design Function And Quantity:** 1 flip-flop, clocked **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 8.0 volts power source **Time Rating Per Chacteristic:** 95.00 nanoseconds propagation delay time, low to high level output and 95.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 10001-2678213 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 flat leads Shelf Life: N/a **Unit Of Measure:**

Fiig:

A458a0

Demilitarization: Yes - demil/mli