## NSN 5962-00-491-4863

Linear Microcircuit - Page 1 of 1

**Demilitarization:** Yes - demil/mli

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-00-491-4863 **Body Length:** 0.395 inches **Body Width:** 0.275 inches **Body Height:** 0.075 inches **Operating Tempurature Range:** -55.0/+100.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and negative outputs and positive outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** Dual 2 input **Design Function And Quantity:** 2 switch, field effect transistor **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -40.0 volts power source and 35.0 volts power source **Time Rating Per Chacteristic:** 150.00 nanoseconds propagation delay time, low to high level output and 150.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 17863-7104104 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 flat leads Shelf Life: N/a **Unit Of Measure:**