NSN 5962-00-491-4898

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-491-4898 **Body Length:** 0.395 inches **Body Width:** 0.395 inches **Body Height:** Between 0.035 inches and 0.075 inches **Operating Tempurature Range:** -55.0/+100.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and high voltage and w/buffered output and positive outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Diode-transistor logic **Input Circuit Pattern:** 12 input **Design Function And Quantity:** 3 buffer and 1 driver, line **Terminal Surface Treatment:** Gold **Voltage Rating And Type Per Characteristic:** -0.3 volts power source and 6.0 volts power source **Time Rating Per Chacteristic:** 60.00 nanoseconds propagation delay time, low to high level output and 60.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold **Test Data Document:** 17863-7104123 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 flat leads Shelf Life: N/a

Yes - demil/mli

Unit Of Measure:

Demilitarization:

NSN 5962-00-491-4898Digital Microcircuit - Page 2 of 2



Fiig:

A458a0