

View Online at <https://aerobasegroup.com/nsn/5962-00-491-9934>

Body Length:

Between 0.330 inches and 0.350 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

0.065 inches

Maximum Power Dissipation Rating:

400.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and high voltage and w/open collector and positive outputs

Inclosure Material:

Ceramic

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Hex 1 input

Design Function And Quantity:

6 buffer and 6 driver

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Time Rating Per Characteristic:

10.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output

Special Features:

Formed leads

Precious Material And Location:

Terminal surface gold

Precious Material:

Gold

Test Data Document:

00752-399759 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0