NSN 5962-00-492-2849

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-492-2849

| Body Outside Diameter: |
|---|
| Between 0.335 inches and 0.370 inches |
| Body Height: |
| Between 0.165 inches and 0.185 inches |
| Maximum Power Dissipation Rating: |
| 450.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -55.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and monolithic and negative outputs and w/buffered output |
| Inclosure Material: |
| Glass and metal |
| Inclosure Configuration: |
| Can |
| Output Logic Form: |
| P-type metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| 4 input |
| Design Function And Quantity: |
| 2 shift register, static |
| Case Outline Source And Designator: |
| T0-100 joint electron device engineering council |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 30.0 volts power source |
| Test Data Document: |
| 12909-401376 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 10 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| |

Fiig:

A458a0