## NSN 5962-00-493-5960

Digital Microcircuit - Page 1 of 2

Yes - demil/mli



View Online at https://aerobasegroup.com/nsn/5962-00-493-5960

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
118.0 milliwatts
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and high speed and monolithic and negative outputs and ac coupled
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Output Logic Form:
Emitter-coupled logic
Input Circuit Pattern:
5 input
Design Function And Quantity:
1 flip-flop, j-k/r-s, clocked
Case Outline Source And Designator:
T0-100 joint electron device engineering council
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
10.0 volts power source
Time Rating Per Chacteristic:
18.00 nanoseconds propagation delay time, low to high level output and 18.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
10 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

## **NSN 5962-00-493-5960**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0