

View Online at <https://aerobasegroup.com/nsn/5962-00-493-5980>

Body Length:

0.450 inches

Body Width:

Between 0.200 inches and 0.300 inches

Body Height:

Between 0.008 inches and 0.100 inches

Maximum Power Dissipation Rating:

300.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and hermetically sealed and positive outputs and high speed and w/enable and synchronous and resettable and complementary outputs and asynchronous

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

9 input

Design Function And Quantity:

1 shift register, universal

Case Outline Source And Designator:

-0-004-ah joint electron device engineering council

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Characteristic:

35.00 nanoseconds propagation delay time, low to high level output and 45.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Test Data Document:

94117-310082 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0