NSN 5962-00-493-6553

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-493-6553
Body Length:
Between 0.240 inches and 0.290 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.030 inches and 0.070 inches
Maximum Power Dissipation Rating:
300.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and negative outputs and positive outputs and w/strobe
Inclosure Material:
Glass and metal
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
Dual 3 input
Design Function And Quantity:
2 comparator, voltage
Case Outline Source And Designator:
T0-91 joint electron device engineering council
Terminal Surface Treatment:
Gold
Time Rating Per Chacteristic:
40.00 nanoseconds propagation delay time, low to high level output
Precious Material And Location:
Body and terminal surfaces gold
Precious Material:
Gold
Test Data Document:
17863-7118963 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig:

A458a0

Yes - demil/mli